

## Ascom i75 VoWiFi Handset

### Features

- VoWiFi Handset with voice, personal alarm and messaging functions
- Robust
- Large, mechanically protected, and scratch-proof display
- Illuminated display
- Headset connector
- Push button alarm
- No-movement and man-down as option
- Time and date indication
- Vibrator alert
- Ring signal easily silenced
- Two different text sizes
- Identity and personal settings stored in handset
- Up to 10 modes with personalized settings
- 3 programmable soft keys for each mode
- 10 programmable hot keys
- Sending/receiving messages
- Voice mail indication<sup>1</sup>
- Manual or automatic keypad lock
- Field upgradable firmware
- Shared phone, supports virtual SIM
- Verified compliance with Cisco Systems, Inc. Cisco Compatible Extension, (CCX) version 2.



### Technical Specifications

#### Physical

Dimension (l x w x d):	134 x 60 x 27
Weight:	145 g (standard battery included)
Material:	Case: PC/ABS and TPE (free from silicone and latex) Keypad: PC/ABS, illuminated by white LEDs
Colour:	Dark grey and Dark steel blue (Protector) Light grey and Dark steel blue (Medic Protector)
Display (w x h):	128 x 64 pixel LCD, illuminated by white LEDs
Clip:	Hinge type (standard) or swivel type

#### Environmental

Operating temperature:	0°C – +40°C
Storage temperature:	-20°C – +70°C

#### Volume

Ring signal:	Adjustable in 5 steps + silent (approx. 100 dB @ 10 cm)
Earpiece:	Adjustable in 10 steps

**Battery**

Type:	1000 mAh or 1800 mAh (Li-Ion)
Speech time <sup>2</sup> / stand-by time:	Up to 4/40 h (1000 mAh) Up to 6/60 h (1800 mAh)
Charging time:	2 – 4 h (1000 mAh) 3 – 6 h (1800 mAh)

**Connectors**

Headset connector:	Contact dealer for information of headset
Battery connector:	For battery charging

**Settings**

Languages:	11 (Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Portuguese, Spanish, and Swedish)
------------	--

**Local Phonebook**

Maximum name length:	22 characters
Maximum number length:	22 digits
Entries:	100

**Telephony**

Indication:	Display, Ring signal (5 different), flashing LED, and vibrator
Answer call:	Button press or automatically
Call list storage capacity:	20 received, dialled and missed calls with time stamp
Protocol:	H.323 with Supplementary Services H.450.1, H.450.2, H.450.3, H.450.4, H.450.6, H.450.7, H.450.8 and H.450.9

**Messaging**

Message length:	System dependent
Storage capacity:	20 messages (maximum 20000 characters)

**Alarm**

Location types:	Associated WLAN access point as standard
Alarm types:	2 push button alarms No-movement and/or Man-down as option

**WLAN**

Number of subscriptions:	4 systems, manual selection
Quality of Service (QoS):	WMM
Supported networks:	802.11b/g

**Security**

Encryption methods:	64/128 bits WEP TKIP
Authentication methods:	Original 802.11 open/shared key authentication WPA-PSK LEAP PEAP-MSCHAPv2 EAP-MD5

For use in Cisco WLAN infrastructure, CCKM is supported to speed up the encryption key exchange when roaming in a multi-cell environment.

**Endurance**

Enclosure protection: IP40, EN 60529  
 Free fall test: IEC 60068-2-32 Ed procedure 1, Dropped 12 times from 1.5 m

**Compliance to European regulations and standards**

EU directives: 73/23/EEC(LVD), 89/336/EEC(EMC) and 1999/5/EC (R&TTE)  
 Product marking: C€  
 RF Spectrum: EN 300 328  
 SAR (Specific Absorption Rate): EN 50360,  
 Normal operation 0.0196 W/kg (10 gram)  
 Safety: EN 60950-1  
 EMC: EN 301 489-17 and EN 301 489-1

**Compliance to US regulations and standards**

Product marking: FCC ID: BXZKATY  
 US: 9FVISNANKATY  
 HAC  
 RF Spectrum: FCC CFR 47 Part 15, paragraph 15.247  
 SAR (Specific Absorption Rate): FCC/OET Bulletin 65  
 Supplement C (2001) and IEEE Std. 1528-2003, December 2003 / ANSI/IEEE Std. C95.1-1999  
 Normal operation 0.036 W/kg (1 gram)  
 Body worn operation 0.117 W/kg (1 gram)  
 Safety: IEC 60950-1  
 CB Bulletin No. 107A, May 2004  
 EMC: FCC Part 15 Class B  
 Hearing aid: 47 CFR Part 68, Subpart D and TIA-968-A

**Compliance to Canadian regulations and standards**

Product marking: IC:3724B-KATY  
 RF Spectrum: RSS-210  
 SAR (Specific Absorption Rate): IEEE Std C95.3-1999  
 Normal operation 0.036 W/kg (1 gram)  
 Body worn operation 0.117 W/kg (1 gram)  
 Safety: IEC 60950-1  
 CB Bulletin No. 107A, May 2004  
 Hearing aid: CS-03

1 System dependent (refers to the voice mail indication feature)

2 Dependent of Active mode, PS-Poll mode, WLAN environment and configuration (refers to the speech time)

Functions	i75 Protector / Medic Protector
Vibrator	Yes
Microphone on/off during call	Yes
Loudspeaking	Yes
Headset connector	Yes
Messaging	Yes
Acknowledge	Yes
Interactive messaging	Yes*
Group messaging	Yes*
Voice mail	Yes*
Data send	Yes
Data with prefix	Yes
Personal alarm	Yes
Alarm with data	Yes
Automatic call after alarm	Yes
Acoustic location signal (ALS)	Yes
Push-button alarm	Yes
Location, access points	Yes
Man-down & No-movement alarm	Option
Availability information/Absence	Yes
Field upgradable software	Yes
* System dependent feature	

*Specifications are subject to change without notice.*